

UNCLASSIFIED

AD NUMBER

AD479655

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors;  
Administrative/Operational Use; 20 MAR 1966.  
Other requests shall be referred to Air Force Rocket Propulsion Lab., Edwards AFB, CA.

AUTHORITY

AFRPL ltr 20 Dec 1971

THIS PAGE IS UNCLASSIFIED

479655

# DOWNEY PLANT

RESEARCH DIVISION

---

PROJECT SOPHY

SOLID PROPELLANT HAZARDS PROGRAM

Technical Documentary Report No.  
AFRPL-TR-66-24

Progress Report On  
Contract AF 04(611)-10919

Report Number 0977-01(02)QP / March 1966 / Copy 192

---

"This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of AFRPL (RPPR-STINFO), Edwards, California 3523."



"When U.S. Government drawings, specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, or in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto."

AEROJET-GENERAL CORPORATION

Research Division  
11711 Woodruff Avenue  
Downey, California

PROGRESS REPORT

PROJECT SOPHY

SOLID PROPELLANT HAZARDS PROGRAM

Technical Documentary Report No.  
AFRPL-TR-66-24

Contract AF 04(611)-10919

0977-01(02)QP

Period Covered: 1 December 1965 - 28 February 1966

Prepared by: R. E. Elwell  
P. K. Salzman  
R. W. Vail, Jr.

Date: 24 March 1966

Reviewed by: M. Nishibayashi  
M. Nishibayashi, Head  
Explosive Kinetics Dept

No. of Pages: 39

Approved by: H. J. Fisher  
H. J. Fisher, Manager  
Research Division

Classification: UNCLASSIFIED

"This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of AFRPL (RPPR-STINFO), Edwards, California 93523."

CONTENTS

	Page No.
1. INTRODUCTION . . . . .	1
2. SUMMARY . . . . .	1
3. THEORY OF CRITICAL GEOMETRY . . . . .	2
3.1 Theoretical Program . . . . .	2
3.2 Experimental Program . . . . .	14
4. LARGE CRITICAL-DIAMETER TESTS . . . . .	23
5. PROPELLANT DEFECTS STUDY . . . . .	25
6. FUTURE PLANS . . . . .	26
REFERENCES . . . . .	27
DISTRIBUTION . . . . .	28

# ILLUSTRATIONS

Figure No.		Page No.
1.	Geometrical Significance of $X$ , $\epsilon$ , and $\xi$ . . . . .	12
2.	Geometric Relationship Between $\epsilon$ and $\xi$ . . . . .	13
3.	Critical Diameter Results -- 7.1% RDX- Adulterated AP-PBAN . . . . .	17
4.	Test Results, Subtask 3.2.2 . . . . .	18
5.	Velocity-Distance Record -- Test 3.2.2.37: Dual Instrumentation, 5.02 in. Diameter, 1.736 gm/cm <sup>3</sup> ; Result, No Go . . . . .	20
6.	Correlation Between Probe Position in Reaction Zone and Oscilloscope Pulse Shape . . . . .	22
7.	Mapping of Reaction Zone Profile, 4-in. Diameter Sample . . . . .	24

# TABLES

Table No.		Page No.
1.	RUBY Calculations for Ammonium Perchlorate . . . . .	3
2.	Covolumes Used in RUBY Code Calculations . . . . .	4
3.	RUBY Calculations for RDX-Wax . . . . .	6
4.	Test Results, Subtask 3.2.2. . . . .	16

## 1. INTRODUCTION

This quarterly progress report is the second of a series which partially fulfills Contract AF 04(611)10919, Large Solid Propellant Boosters Explosive Hazards Study Program. The purpose of this program is to gain additional knowledge and to develop new techniques for analyzing the explosive hazard and damage potential of large solid-propellant rocket motors.

The objectives of this program are: (1) to determine the influence of grain shape on propellant detonability and sensitivity, (2) to determine the critical diameter of a typical solid rocket-motor propellant, (3) to determine what changes a solid propellant grain might undergo when exposed to operational mishaps, and (4) to develop methods to simulate and characterize these alterations.

## 2. SUMMARY

- o Air Force approval of the program plan, Reference 1, was received 8 December 1965.
- o The RUBY computer code has been successfully applied to ammonium perchlorate, RDX, and RDX-wax. A revision of RUBY is being acquired which will allow the formation of more than one solid product by the reaction.
- o The variance and critical geometry tests of AAB-3189 have been delayed because of casting-line difficulties in preparing the RDX-adulterated material.
- o Critical diameter and variance tests of one batch of AAB-3225 have been completed. From the test results, the critical diameter is 5.21 in. and the experimental standard deviation is 0.06 in.
- o Preliminary tests in the development of a probe system for measuring reaction-zone thickness in a detonating charge have shown encouraging results.
- o The explosive booster and propellant acceptor segments have been cast for the 72-in. critical-diameter test scheduled for late March. All handling hardware, lifting fixtures, restraining fixtures, and other tooling have been completed and checked out.



- o The first 2500-lb TNT calibration charge has been cast for the instrumentation checkout and calibration shot which will be fired in early March. The test will be repeated, using a second charge, after the 72 in. test has been performed.

### 3. THEORY OF CRITICAL GEOMETRY

#### 3.1 THEORETICAL PROGRAM

##### 3.1.1 Ammonium Perchlorate Detonation Properties

After considerable analysis of the RUBY program in an effort to discover the cause for its failure to provide a solution for the ammonium perchlorate (AP) detonation properties, the trouble was located and identified as an error in input. The error was corrected, and satisfactory solutions were generated for ammonium perchlorate at each of several loading densities. Computed detonation properties for AP at densities of 1.50 and 0.08 g/cm<sup>3</sup> are presented in Table 1.

These values are in agreement with the results calculated for ammonium perchlorate by Evans, et al, (Reference 2), using RUBY. The particular loading densities chosen by Aerojet unfortunately did not coincide with those selected in Reference 2. To make a comparison between the two sets of data would require interpolation. Evans, et al, report an ideal detonation velocity for AP of 3.67 mm/μsec at a loading density of 0.75 g/cm<sup>3</sup> and 4.13 mm/μsec at 0.95 g/cm<sup>3</sup>. The Aerojet calculations yielded a velocity of 3.82 mm/μsec at a loading density of 0.080 g/cm<sup>3</sup>, and an interpolated velocity of 4.20 mm/μsec at 0.95 g/cm<sup>3</sup>.

The small differences between the two sets of calculations may result from the differences in the covolume inputs used, since some uncertainty exists as to the correct covolume values for specific compounds. RUBY is particularly sensitive to covolume input values. The values used in the work by Evans, et al, are not reported. Those used in the Aerojet calculations are given in Table 2.



Table 1. RUBY Calculations for Ammonium Perchlorate.

Property	Units	$\rho_o = 0.80$ g/cc	$\rho_o = 1.50$ g/cc
D	mm/ $\mu$ sec	3.824	5.554
$P_{C-J}$	Mbar	0.032	0.110
$T_{C-J}$	$10^3$ °K	1.227	0.795
$\rho_{C-J}$	gm/cc	1.105	1.968
$\gamma$	(dimensionless)	2.621	3.208
$E_{C-J} - E_o$	cal/gm HE	133.3	208.1
$S_{C-J} - S_o$	cal/°K/gm/HE	-0.346	-0.834
$\Sigma$ moles gas	$10^{-3}$ moles/gm HE	36.32	36.32
$V_g$	cc/mole	24.91	13.99
<u>Composition</u>			
H <sub>2</sub> O	$10^{-3}$ moles/gm HE	12.82	12.82
N <sub>2</sub>	$10^{-3}$ moles/gm HE	4.27	4.27
O <sub>2</sub>	$10^{-3}$ moles/gm HE	10.68	10.67
NO <sub>2</sub>	$10^{-3}$ moles/gm HE	0.00	0.01
HCl	$10^{-3}$ moles/gm HE	8.56	8.55

Symbols

D                   detonation velocity  
 $\rho, T, \gamma, E, S, V$    standard thermodynamic quantities

Subscripts

C-J               Chapman-Jouguet conditions  
o               original condition  
g               gas

Table 2. Covolumes Used in RUBY Code Calculations.

<u>Product</u>	<u>RDX-Wax</u>	<u>Ammonium Perchlorate</u>
H <sub>2</sub> O	360	250
H <sub>2</sub>	180	180
CO <sub>2</sub>	670	-
N <sub>2</sub>	380	380
O <sub>2</sub>	350	350
NO <sub>2</sub>	600	600
NH <sub>3</sub>	476	476
CH <sub>4</sub>	528	-
HCl	-	643

Experimental detonation velocities for AP, at various densities and charge diameters, are reported by Andersen and Pesante (Reference 3). At a loading density of  $0.80 \text{ g/cm}^3$  and a charge diameter of 4 in. the detonation velocity was observed to be  $3.0 \text{ mm}/\mu\text{sec}$ . Furthermore, from the shape of their velocity-diameter curve, ranging from a diameter of 0.75 in. to the 4 in., it appears that  $3.0 \text{ mm}/\mu\text{sec}$  approaches the ideal detonation velocity. The RUBY program is approximately 25% high with its calculation of  $3.82 \text{ mm}/\mu\text{sec}$ .

Three separate experimental values are reported in Reference 3 for AP detonation velocity at a packing density of  $1.50 \text{ g/cm}^3$ . The values were obtained from 2.5 in. diameter samples, and averaged to  $4.3 \text{ mm}/\mu\text{sec}$ . No evidence is given to indicate that 2.5 in. is near the ideal diameter at this density, therefore data are not to be compared with the predicted  $5.55 \text{ mm}/\mu\text{sec}$  ideal velocity.

### 3.1.2 RDX-Wax Detonation Properties

RUBY calculations also have been made for an explosive composed of 30 wt % RDX and 70 wt % wax - a material similar to that which was used in the AF 04(611)9945 program. The purposes of making these calculations were: (1) to compare the experimental detonation-velocity results obtained in the nonideal region with the calculated ideal detonation velocity, and (2) to test the ability of RUBY to handle a composition similar to a composite propellant -- fast-reacting oxidizer distributed in a slow-reacting fuel. The results of these computations are given in Table 3.

The detonation-velocity vs diameter relationship of RDX-wax (Reference 4) indicates that the ideal detonation velocity is greater than  $6.5 \text{ mm}/\mu\text{sec}$  ( $D = 6.57 \text{ mm}/\mu\text{sec}$  at  $d = 1.75 \text{ in.}$  for the material, which has a critical diameter of approximately 1.5 in.). The upper bound would appear to be  $7.2 \text{ mm}/\mu\text{sec}$ . This is based on an extrapolation of the data which is influenced by the fact that the velocity-diameter function for this type of material closely approaches its asymptote  $D_i$  at diameters  $d \geq 2 d_c$ . The RUBY program predicts an ideal detonation velocity of  $6.9 \text{ mm}/\mu\text{sec}$  when the input parameter, heat of formation of graphite, is chosen to be zero (Table 3). With the heat of formation of carbon chosen to be  $10.75 \text{ kcal/mole}$ , as it has been for SR1 and NOTS, RUBY predicts an ideal detonation velocity of  $6.2 \text{ mm}/\mu\text{sec}$ . The first computation which agrees with the experimental evidence is encouraging and indicates that RUBY can handle a propellant-like material as well as the high explosives, for which the program was originally written.

Table 3. RUBY Calculations for RDX-Wax.

$$\rho_o = 1.11 \text{ g/cc}$$

Property	Units	$\Delta H_f$ of Graphite = 0. 0 Kcal/mole	$\Delta H_f$ of Graphite = 10. 75 Kcal/mole
D	mm/ $\mu$ sec	6. 906	6. 211
P <sub>C-J</sub>	Mbar	0. 123	0. 091
T <sub>C-J</sub>	10 <sup>3</sup> °K	1. 058	0. 707
$\rho_{C-J}$	gm/cc	1. 444	1. 408
$\gamma$	(dimensionless)	3. 315	3. 729
E <sub>C-J</sub> - E <sub>o</sub>	cal/gm HE	306. 5	206. 1
S <sub>C-J</sub> - S <sub>o</sub>	cal/°K/gm/HE	-0. 844	-1. 112
$\Sigma$ moles gas	10 <sup>-4</sup> moles/gm	349. 168	351. 437
V <sub>g</sub>	cc/mole	15. 89	16. 76
<u>Composition</u>			
H <sub>2</sub> O	10 <sup>-4</sup> moles/gm HE	80. 993	39. 776
H <sub>2</sub>	10 <sup>-4</sup> moles/gm HE	0. 002	--
CO <sub>2</sub>	10 <sup>-4</sup> moles/gm HE	0. 003	20. 612
N <sub>2</sub>	10 <sup>-4</sup> moles/gm HE	35. 816	40. 376
NH <sub>3</sub>	10 <sup>-4</sup> moles/gm HE	9. 368	0. 248
CH <sub>4</sub>	10 <sup>-4</sup> moles/gm HE	222. 967	250. 425
C (graphite)	10 <sup>-4</sup> moles/gm HE	--	269. 962
C (diamond)	10 <sup>-4</sup> moles/gm HE	318. 029	--
<u>Symbols</u>			
D	detonation velocity		
$\rho, T, \gamma, E, S, V$	standard thermodynamic quantities		
<u>Subscripts</u>			
C-J	Chapman-Jouguet conditions		
o	original condition		
g	gas		

The low, 1058°K, C-J temperature, predicted by RUBY, is of some concern. However, the extremely low oxygen content in the material does suppress the reaction kinetics and may do so to sufficiently account for this temperature. Since no experimental measurement of this temperature has been made, it is not possible to reject the value calculated by RUBY.

### 3.1.3 AP-Binder Systems Detonation Properties

A later version of the RUBY code is being obtained from the Naval Ordnance Test Station (NOTS), China Lake, California. This program, in conjunction with NOTS thermodynamic data, has been successfully used to calculate the ideal detonation properties of several AP-binder systems. It is intended to use this program and the NOTS data to calculate the ideal detonation properties for an RDX-adulterated AP-PBAN composition (AAB-3189) and an unadulterated AP-PBAN composition (ANB-3226). Detonation velocities in the adulterated material will be measured experimentally, to diameters in excess of 4  $d_c$  (Subtask 3.2.3).

### 3.1.4 Estimation of Density-Variation Effect on Parameter $c$

In the theory developed under AF 04(611)9945,

$$d_c = k_1 + k_2 (f + c)^{-1/3} \quad (1)$$

where  $d_c$  is the critical diameter of a propellant material containing  $f$  weight fraction RDX, and  $k_1$ ,  $k_2$ , and  $c$  are constants. The parameter  $c$  represents the excess weight fraction RDX that would exist if all effective voids\* were replaced by RDX particles of comparable size. It can be shown that if  $W_R$  = actual weight of RDX and  $W_R^i$  = weight of RDX "added",

$$c = \frac{1 + \left(\frac{W_R^i}{W_R}\right)}{\left(\frac{1}{f}\right) + \left(\frac{W_R^i}{W_R}\right)} - f \quad (2)$$

\*"Effective voids" means those voids capable of becoming initiation sites by shock-compression.

Furthermore, the quotient term can be expressed by

$$\frac{W'_R}{W_R} = \left( \rho_R / \rho_o \right) \left( \frac{1}{f} \right) N_v \bar{V}_v \quad (3)$$

where

$\rho_R$  = density of RDX

$\rho_o$  = porous propellant density

$N_v$  = number of effective voids per unit volume

$\bar{V}_v$  = average volume of the effective voids

From Equation 32 in Reference 5, the distribution of voids can be expressed by

$$N = n_p \exp \left( -V/V_a \right) \quad (4)$$

where

$N$  = number of voids per unit volume greater than volume  $V$

$n_p$  = total number of voids per unit volume

$V_a$  = the average void volume

If  $V_i$  is the minimum effective void volume,

$$N_v = n_p \exp \left( -V_i/V_a \right) \quad (5)$$

The average void size,  $\bar{V}$ , over any interval can be calculated from

$$\bar{V} = \frac{\int_{V_1}^{V_2} V f(V) dV}{\int_{V_1}^{V_2} f(V) dV} \quad (\text{Reference 6}) \quad (6)$$

where

$$f(V) = \frac{d}{dV} \left[ 1 - \left( \frac{N}{n_p} \right) \right] \quad (7)$$



Integrating Equation 6 between  $V_i$  and  $\infty$ , it can be shown that

$$\bar{V}_v = V_i + V_a \quad (8)$$

Considering the product  $N_v \bar{V}_v$  in Equation 3, from Equations 5 and 8

$$N_v \bar{V}_v = n_p (V_i + V_a) \exp(-V_i/V_a) \quad (9)$$

Substituting  $(1 - \rho_o/\rho_{on})/n_p$  for  $V_a$ , Equation 9 becomes

$$N_v \bar{V}_v = \left[ V_i n_p + 1 - (\rho_o/\rho_{on}) \right] \exp \left[ -V_i n_p / 1 - (\rho_o/\rho_{on}) \right] \quad (10)$$

where

$\rho_{on}$  = the density of nonporous propellant

From Equations 30 through 37 in Reference 5 it can be shown that

$$V_i n_p = 3C_2/D^2 \quad (11)$$

where

$C_2$  = a constant

$D$  = the detonation velocity

Substitution of Equations 3, 10, and 11 into Equation 2 gives the final expression for  $c$  as a function of  $\rho_o$ , knowing  $f$ ,  $C_2$ ,  $\rho_R$ , and  $D$ :

$$c = \frac{1 - f}{1 + \frac{[\rho_o \exp 3C_2/D^2 (1 - \rho_o/\rho_{on})]}{\rho_R [(3C_2/D^2) + 1 - (\rho_o/\rho_{on})]}} \quad (12)$$

Equation 12 and others in this development will be written into a computer program to facilitate the calculations required to compute the values of many of the parameters discussed.



### 3.1.5 Error Analysis of Probe-Rasteroscillograph Data

The propagation-of-error technique has been applied to shock wave velocity vs distance data as derived from pin-probe/rasteroscillograph distance-time data. It can be shown that

$$\frac{V(D)}{D^2} = 2 \left[ \frac{V(x)}{(\Delta x)^2} + \frac{V(t)}{(\Delta t)^2} \right] \quad (13)$$

where the symbol  $V( )$  refers to the variance, or standard deviation squared, of the parenthetical quantity,  $x$  is distance along the charge from the initiated end,  $t$  is the time of arrival of the shock front, and  $\Delta x$  is the interval over which the velocity is determined ( $\Delta t$  is the time interval associated with  $\Delta x$ ).

If  $X$  is the distance from the sample top (initiated end) to the probe-entrance hole,  $\delta$  is the displacement of the probe tip from a plane perpendicular to the sample axis through the probe-entrance hole, and  $\epsilon$  is the effective displacement of the probe tip because of its deflection from the plane of the sample axis and probe-entrance hole and the curvature of the wave front, the distance  $x$  between the probe tip and the initiated end of the sample is

$$x = X + \delta + \epsilon \quad (14)$$

and

$$V(x) = V(X) + V(\delta) + V(\epsilon) \quad (15)$$

Evaluating the terms in Equation 15, we find that by definition,

$$V(X) = \sigma_X^2 \quad (16)$$

and that

$$V(\delta) = \cos^2 \phi V(l) + l^2 V(\cos \phi) \quad (17)$$

and

$$V(\epsilon) = \frac{(r - \ell)^2}{R^2 - (r - \ell)^2} V(\ell) + \frac{\xi^2}{R^2 - \xi^2} V(\xi) \quad (18)$$

where

$\phi$  = the colatitude of the probe tip with respect to the probe-entrance-holes line

$\ell$  = is the length of the probe that is inserted into the sample

$r$  = the sample radius

$R$  = the radius of curvature of the wave front

$\xi$  = the distance from the probe tip to the sample axis

$$\xi^2 = r^2 - 2 r \ell \sin \phi \sin \theta + \ell^2 \sin^2 \phi$$


where

$\theta$  = the longitude of the probe tip with respect to the plane tangent to the sample at the probe-entrance-holes line.

The geometrical relationships of the parameters discussed in Equations 14 through 19 are shown in Figures 1 and 2.


Assuming the following values for the parameters:  $\sigma_X = 1.59$  mm,  $\phi = \theta = 89^\circ$ ,  $\sigma_\phi = \sigma_\theta = 1^\circ$ ,  $\ell = 38$  mm,  $\sigma_\ell = 1.59$  mm, for a sample of 5-in. diameter ( $r = 63.5$  mm) the estimated coefficient of variance for velocity data is computed by the above equations to be 0.053. That is, the estimation of velocity has an expected error of  $\pm 5.3\%$ , which for a sample detonating at 4.1 mm/ $\mu$ sec represents a standard deviation of 0.22 mm/ $\mu$ sec.

An experimental study, using two sets of probes in a 5-in. diameter sample, was performed in conjunction with Subtask 3.2.2 testing, and from the analysis of these data a coefficient of variance was calculated to be 0.051. This result substantiates the essential accuracy of this analysis. The results have shown furthermore that greater efforts at accurate probe-placement are required. Design studies are now underway to achieve this objective.



- X-axis: Probe-entrance-holes line. increasing X is increasing distance from sample top.  
 XY-plane: Plane through sample axis and X.  
 XZ-plane: Plane tangent to sample at X-axis.  
 X : Distance of probe-entrance hole from sample top.  
 $\phi$  : Colatitude of probe tip.  
 $\theta$  : Longitude of probe tip.  
 l : Length of probe inserted into sample.  
 $\delta$  : Vertical displacement of probe tip.  
 $\xi$  : Distance of probe tip from sample axis.

Figure 1. Geometrical Significance of X,  $\delta$ , and  $\xi$ .



- $R$  : radius of curvature of wavefront, exaggerated.
- $\xi$  : probe-tip to sample-axis distance.
- $r-l$  : minimum  $\xi$
- $r$  : sample radius
- $\epsilon$  : "equivalent vertical displacement" of probe tip, due to its being  $\delta-(r-l)$  farther from the sample axis.

Figure 2. Geometric Relationship Between  $\epsilon$  and  $\xi$ .

### 3.2 EXPERIMENTAL PROGRAM

#### 3.2.1 Variance and Mean Critical Geometry

This subtask is designed to produce sufficient experimental data for a statistical analysis of the variance in critical geometry test results. Two configurations will be tested, a circular right cylinder and a square right column. The test samples are composed of AAB-3189 propellant, an Aerojet RDX-adulterated AP-PBAN formulation containing 9.2 wt % RDX explosive. The material is the same as that used in the critical geometry phase of AF 04(611)9945. Its critical diameter was found to be 2.71-in., with an estimated standard deviation of 0.06-in.

A 2000-lb batch of AAB-3189 was cast 17 January 1966. This batch consisted of (1) 50 cylindrical samples cast at 2.80, 2.74, 2.68, and 2.62-in. diameter, (2) six square columns (two each of the following sizes: 2.4, 2.5, 2.6-in. square), and (3) eight samples for Subtask 3.2.3 tests. The number of small cylinders cast at each size was selected in accordance with statistical design to provide optimum advantage to the determination of the variance. While the critical diameter may differ slightly from 2.71-in., it is not expected that it will approach the extreme diameters chosen for this set of tests.

The square samples provide sizes for a crude bracketing of the critical geometry for this shape. The sizes are based on the results of tests conducted with RDX-wax under AF 04(611)9945, which indicated that the critical geometry of a square column is at least 10% below the critical diameter.

The cured samples were subjected to X-ray inspection on 28 and 31 January 1966. A large number of major voids (larger than 1/4 in. diameter) were found in many of the samples. Of the 50 cylindrical samples intended for this subtask, only five were without voids. The cause was a vacuum leak in one of the two transfer-pot systems. This leak allowed air to mix with the viscous propellant during the casting operation.

To prevent the recurrence of such an incident, the following procedure has been incorporated into the casting operation. A preliminary sample will be cast and X-rayed immediately so that voids can be detected before the full batch is cast. The propellant transfer system will be closely examined for any evidence of vacuum leakage.



The second casting of this batch has been scheduled for 1 March, so that samples will be available for testing by approximately 1 April.

### 3.2.2 Mean Critical Diameter and Variance

The test objective is to accurately determine the critical diameter of an adulterated AP-PBAN propellant containing 7.1 wt % RDX (AAB-3225) and to estimate the variance of the results. The specific purposes of these tests are: (1) to evaluate the ability of the detonation model to predict the critical diameter of a specific material, (2) to obtain variance data at an RDX-adulterant level other than 9.2%, and (3) to find by extrapolation, the variance expected for 0% RDX (unadulterated) AP-PBAN.

#### 3.2.2.1 Test Results

The results of the 37 tests are shown in Table 4 and in Figures 3 and 4. The mean critical diameter is 5.21 in., with a standard deviation of 0.06 in.

Since the predicted critical diameter was 6.00 in., most of the test samples had to be cut and machined to smaller diameters for these tests. In the process of making these modifications, it was necessary to limit the length of some samples to four-diameter lengths; others were capable of being machined to five-diameter lengths.

The data in Table 4 are arranged in order of decreasing diameter and, for samples having the same diameter, they are arranged in order of increasing density. The X-ray reports from this batch of propellant showed that every sample had some major voids. All but three samples had these voids in the upper 1- or 2-in. area. It was decided to proceed with the testing of all but the worst sample (No. 37) since the orientation of the sample in the test setup was in the as-cast position, with the major voids at the upper end. The presence of holes at the initiated end did not compromise the data taken over the lower half of the sample.

Table 4. Test Results, Subtask 3.2.2.

Diameter		Density (gm/cm <sup>3</sup> )	Result (+ = Go 0 = No Go)	Average Detonation Velocity <sup>a</sup> (mm/μsec)	Test No.
Mean (in.)	σ (in.)				
6.29	-	1.735	+	4.2	3.2.2.2
5.65	-	1.734	+	b	3.2.2.1
5.65	-	1.734	+	4.1	3.2.2.3
5.45	0.034	1.725	+	4.2	3.2.2.6
5.38	0.018	1.739	+	4.2	3.2.2.9
5.37	0.011	1.740	+	4.3	3.2.2.11
5.35	0.025	1.739	+	4.2	3.2.2.8
5.34	0.033	1.736	+	4.2	3.2.2.16
5.34	0.031	1.740	+	4.2	3.2.2.14
5.34	0.027	1.741	+	4.2	3.2.2.15
5.30	0.025	1.733	+	4.3	3.2.2.13
5.29	0.024	1.730	+	4.1	3.2.2.21
5.29	0.021	1.731	+	4.2	3.2.2.22
5.28	0.023	1.731	+	4.2	3.2.2.23
5.28	0.036	1.731	+	4.2	3.2.2.26
5.28	0.028	1.732	+	4.2	3.2.2.24
5.28	0.027	1.733	+	4.2	3.2.2.28
5.28	0.010	1.735	+	b	3.2.2.12
5.28	0.017	1.736	+	4.1	3.2.2.18
5.28	0.016	1.736	+	4.2	3.2.2.19
5.28	0.011	1.736	+	4.2	3.2.2.20
5.28	0.018	1.737	0	c	3.2.2.17
5.28	0.008	1.739	0	c	3.2.2.10
5.27	0.008	1.743	0	c	3.2.2.5
5.25	0.040	1.730	+	4.1	3.2.2.25
5.24	0.024	1.733	+	4.0	3.2.2.27
5.24	0.025	1.733	+	4.1	3.2.2.29
5.02	0.010	1.729	0	c	3.2.2.7
5.02	0.016	1.736	0	c	3.2.2.37
5.01	0.003	1.733	0	c	3.2.2.4
5.01	0.016	1.735	0	c	3.2.2.30
4.86	0.011	1.739	0	c	3.2.2.35
4.85	0.015	1.735	0	c	3.2.2.34
4.85	0.014	1.736	0	c	3.2.2.36
4.75	0.011	1.738	0	c	3.2.2.31
4.74	0.008	1.731	0	c	3.2.2.32
4.50	0.015	1.735	0	c	3.2.2.33

<sup>a</sup> Calculated from probe data. Obtained over region from two diameters down, to charge bottom. Accuracy of measurement is  $\pm 0.1$  mm/μsec.

<sup>b</sup> No raster record.

<sup>c</sup> Not applicable.






Figure 3. Critical Diameter Results -- 7.1% RDX-Adulterated AP-PBAN.




Figure 4. Test Results, Subtask 3.2.2.

### 3.2.2.1.1 Density Measurements

The density measurements on these samples yielded an average density of  $1.735 \text{ gm/cm}^3$  with a standard deviation of  $0.04 \text{ gm/cm}^3$ . Using these data and assuming the maximum (no pores) density to be  $3\sigma$  above the mean, the data indicate that  $\rho_{0n}$  is  $1.747 \text{ gm/cm}^3$ .

Observations during the casting proceedings, where slumping of the propellant was reported, gave another source by which the maximum density could be estimated. In the 6-in. diameter samples, when vacuum was released, the propellant surface dropped about 3-in. This drop can be related to the volume of included gas. In subsequent calculations using this data, a porosity of 0.008 is predicted. Assuming that this porosity is that equivalent to a density of  $1.735 \text{ g/cm}^3$ , the nonporous density becomes  $1.749 \text{ g/cm}^3$ . This agrees with the value calculated from density measurements even though it was based on approximate information. However, when these values are used with Equation 2, a value of  $c$  is calculated which equals  $1.4 \times 10^{-4}$ . This is not in agreement with the value of  $c$  which statistically best-fits the critical-diameter data. Further study of this problem is being conducted.

### 3.2.2.1.2 Velocity Accuracy

To test the analysis that is presented in Section 3.1.3, a test was conducted using a 5-in. diameter sample. Probes were placed along two diametrically opposite lines down the sample, with probes placed at corresponding distances from the top. By comparing the velocities derived across each pair of intervals, the coefficient of variance was calculated to be 0.051. The detonation-velocity vs distance record is shown in Figure 5.

### 3.2.2.2 Conclusions and Future Work

Statistical analysis of the AAB-3225 data presented in Table 4 and Figures 3 and 4 yielded a mean critical diameter of 5.21-in., with a standard deviation of 0.06 in. This critical diameter is about 13% below the theoretically predicted value of 6.00 in. The standard deviation, on the other hand, is the same as that derived for AAB-3189 during the SOPHY I critical-diameter tests. This agreement indicates that variance is relatively constant in the region; 7.1% to 9.2% RDX (5.21- to 2.71-in. critical-diameter).




Figure 5. Velocity-Distance Record -- Test 3.2.2.37: Dual Instrumentation, 5.02 In. Diameter, 1.736 gm/cm<sup>3</sup>; Result, No Go.

The surprisingly low value of the standard deviation implies that either the critical diameter of the material is not greatly affected by the presence of a number of voids of the size present in these samples, or the void effect was unusually consistent from sample to sample. If the latter is true, the lack of agreement between the experimental data and the model may be attributed to the effective lowering of the critical diameter by the porosity.

The uncertain results from these tests forced the re-casting of this batch on 18 February 1966. No propellant slumping was observed when vacuum was released. The sample sizes selected span the region from 5- to 7-in. as follows: two at 5 in., two at 5-1/4 in., two at 5-1/2 in., three at 5-3/4 in., five at 5-7/8 in., four at 6 in., five at 6-1/8 in., two at 6-1/4 in., two at 6-1/2 in., and two at 7 in. Should the initial tests of these samples support the current critical-diameter estimate, it may become unnecessary to test the entire batch.

### 3.2.3 Detonation Velocity as a Function of Size

Preliminary tests have been performed in order to perfect the probe and electronic circuitry necessary for reaction-zone measurement. These tests were formed to determine detonation velocity and reaction-zone thickness as functions of size.

Special ionization probes, constructed from drill rod, in combination with a constant-voltage source, in a voltage-divider circuit, are used for this system. The voltage across a known resistor placed in series with the probe is monitored on an oscilloscope. The changes in voltage across the resistor are inversely related to changes in resistance across the probe gap during passage of the highly-ionized reaction zone. Assuming constant ion-concentration throughout the reaction zone, the voltage drop across the resistor is proportional to the length of the probe inside the reaction zone. Thus the shape of the pulse on the oscilloscope is a projection of the reaction-zone profile in the sector that is intercepted by the probe. The amplitude of the pulse can be equated to the distance the probe is inserted into the sample. (The maximum distance is the sample radius, by symmetry.) With the wave moving at a constant velocity, time units can be converted to distance units in the direction of the sample axis. The time axis (zero volts) is equivalent to a line through the probe tip parallel to the axis. A representation of this concept is shown in Figure 6.






Figure 6. Correlation Between Probe Position in Reaction Zone and Oscilloscope Pulse Shape.

The results from one of the preliminary tests are shown in Figure 7, where the close agreement between probes inserted to different depths is shown. One probe was inserted to the sample axis. The pulse resulting from this probe will show the profile of one-half the reaction zone. The second probe was inserted one-half radius toward the axis; its output will show the shape of the outer portion only of the zone which envelopes the probe. The overlapping of these traces, when an appropriate scale adjustment was made, indicated good support for the basic hypothesis upon which this method is based. The only adjustment required was to shift zero-time on the pulse obtained from the shorter probe to that time on the longer pulse which represented the time of arrival of the front to the tip of the short probe. The agreement in rising and falling slopes was excellent.

Subsequent tests of this system, with an explosive linewave generator, showed that the inherent rise time was better than 0.2  $\mu$ sec. Since the rise times of these pulses was near 4  $\mu$ sec, no serious masking of the wavefront curvature could be attributed to the electronic system, and therefore considerable confidence could be placed in the curvature deduced from the pulse shape.


#### 4. LARGE CRITICAL-DIAMETER TESTS

The five segments have been cast in preparation for testing the 72-in.-diameter unadulterated propellant sample. The segments have been removed from the curing ovens for final surface finishing. X-ray inspection and preparation for shipment to Area 1-36D, AFRPL, are the items on the immediate schedule. The target date for the test remains set at 25 March 1966.

The vacuum chuck fabrication is completed and the fixture is ready to be checked out. The other handling fixtures also have been fabricated.

The TNT booster, consisting of stacked segments to approximate a 3:1 cone, has been cast at Aerojet's Chino Hills facility, along with a 2-ft diameter x 8-ft high TNT cylinder which is to be fired in early March in order to check out all instrumentation systems for the 72-in.-diameter test.





2842-2-7-1

Figure 7. Mapping of Reaction Zone Profile, 4-in. Diameter Sample.

Of considerable importance in the calibration test is the checkout of the detonation-velocity probe systems. Several changes have been made to the system that was employed in the 48-in.-diameter tests performed on AF 04(611)9945. These will be evaluated in the TNT shot, and the system that performs the best will be used in the 72-in.-diameter test. The problem experienced last year was the reception of extensive noise, which made the rasteroscillograph records difficult, and in some cases impossible, to read.

Aerojet personnel are currently involved in the preparation of the test site for these two tests. Preparation includes considerable modification of the electronic instrumentation to improve the capabilities of the area and its efficient operation. Instrumentation pits are being cleaned out and new lids, to permit more effective sealing of the pits, are being fabricated and will be installed soon.

#### 5. PROPELLANT DEFECTS STUDY

The literature search is continuing. A complete summary and bibliography of the search will be issued upon completion of this project.

An experimental program to develop and evaluate means of producing and characterizing propellant with defects will soon begin. Efforts have been limited to a study of the directions most likely to be successful in this subtask.

After discussions with Dr. Frank Hepner of the Propellant Development Department at Research and Technology Operations, Sacramento, California, it was decided that this group has both the experience and capabilities to undertake the major portion of this investigation. Work will commence after the defects study program details have been agreed upon. It is expected that the planning of this effort will require most of the month of March, which will make 1 April the target date for beginning the study.

## 6. FUTURE PLANS

During the next quarterly period, March through May 1966, the following work will be performed:

- a. Completion of the variance and mean critical-geometry tests (Subtasks 3.2.1 and 3.2.2).
- b. Near-completion of Subtasks 3.2.3 and 3.2.4\*.
- c. Firing of the 72-in.-diameter test, selection and casting the second large critical-diameter sample.
- d. Certain parts of the Phase II test program may be initiated depending on the results of the 72-in.-diameter test.
- e. Continuation of the propellant defects literature search.
- f. Initiation of the propellant defects experimental program.
- g. Continuation of microscopic analysis of each batch of adulterated propellant, for information pertinent to the estimation of the parameter  $c$  in the detonation model.
- h. Use of RUBY to compute detonation properties of composite propellant.

---

\*Jetting phenomena study.

#### REFERENCES

1. Program Plan, Project SOPHY, Solid Propellant Hazards Study, Aerojet-General Report 0977-01(01)ER, 14 November 1965.
2. Evans, M. W., Reese, B. O., Seely, L. B., and Lee, E. L., "Shock Initiation of Low-Density Pressings of Ammonium Perchlorate," The Fourth Symposium on Detonation (Preprints, Vol. II), U.S. Naval Ordnance Laboratory, White Oak, Silver Springs, Md., pp C-78 through C-89 (October 12-15, 1965).
3. Andersen, W. H. and Pesante, R. E., "Reaction Rate and Characteristics of Ammonium Perchlorate in Detonation," Eighth Symposium (International) on Combustion, The Williams and Wilkins Co., Baltimore, Md., pp 705-710 (1962).
4. Large Solid-Propellant Boosters Explosive Hazards Study Program (Project SOPHY), Technical Documentary Report AFRPL-TR-65-211, Aerojet Report 0866-01(01)FP (November 1965).
5. Salzman, P. K., Irwin, O. R., and Andersen, W. H., "Theoretical Detonation Characteristics of Solid Composite Propellants," AIAA Journal, Vol. 3, No. 12, pp 2230 - 2238 (December 1965).
6. Mood, A. F., Introduction to the Theory of Statistics, McGraw-Hill Book Company, Inc., New York (1950).



# DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1 ORIGINATING ACTIVITY (Corporate author) <b>Aerofet-General Corporation Downey, California</b>		2a REPORT SECURITY CLASSIFICATION <b>Unclassified</b>	
		2b GROUP <b>N/A</b>	
3 REPORT TITLE <b>PROJECT SOPHY - SOLID PROPELLANT HAZARDS PROGRAM</b>			
4 DESCRIPTIVE NOTES (Type of report and inclusive dates) <b>Progress Report. 1 December 1965-28 February 1966</b>			
5 AUTHOR(S) (Last name, first name, initial) <b>Elwell, R. B. Salzman, P. K. Vail, R. W., Jr.</b>			
6 REPORT DATE <b>March 1966</b>		7a TOTAL NO OF PAGES <b>39</b>	
		7b NO OF REFS <b>6</b>	
8a CONTRACT OR GRANT NO. <b>AF 04(611)10919</b>		9a ORIGINATOR'S REPORT NUMBER(S) <b>0977-01(02)QP</b>	
b. PROJECT NO. <b>623A00201</b>		9b OTHER REPORT NO(S) (Any other numbers that may be assigned this report) <b>AFRPL-TR-66-24</b>	
10 AVAILABILITY/LIMITATION NOTICES <b>Qualified requestors may obtain copies of this report from DDC.</b>			
11 SUPPLEMENTARY NOTES		12 SPONSORING MILITARY ACTIVITY <b>AFRPL, Hazards Analysis Branch AF Systems Command, Edwards AFB Edwards, California</b>	
13 ABSTRACT <b>Theoretical and experimental investigations of the detonation characteristics of solid composite propellant rocket-motor grains are described. Statistical variance in critical-diameter data was determined for an RDX-adulterated AP-PBAN propellant. Preparations for a large critical-diameter test, involving unadulterated AP-PBAN propellant, are discussed.</b>			

## KEY WORDS

DAR ATAG JOSTWOC

## LINK A

## LINK B

## LINK C

## ROLE

## WT

## ROLE

## WT

## ROLE

## WT

Hazards

Solid Propellant

SOPHY

Critical Diameter

Critical Geometry

## INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, &c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through \_\_\_\_\_."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through \_\_\_\_\_."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through \_\_\_\_\_."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.